

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **08-011921**

(43)Date of publication of application : **16.01.1996**

(51)Int.Cl.

B65D 47/34

B05B 1/02

B05B 7/04

B05B 9/04

(21)Application number : **06-164498**

(71)Applicant : **YOSHINO KOGYOSHO CO LTD**

(22)Date of filing : **23.06.1994**

(72)Inventor : **IIZUKA SHIGEO
SAITO TADAO**

(54) **FOAM JET CONTAINER**

(57)Abstract:

PURPOSE: To jet ideal foam when a container is either in a normal position or in an inverted position, minimize a possibility of intrusion of liquid into an air cylinder, and prevent occurrence of an operational failure of a pump.

CONSTITUTION: Leak of liquid is prevented even if a container is inverted by providing a pressure reduction-preventing valve 22 of a special construction. Contained liquid can be sucked either in a normal position or in an inverted position by providing a change-over valve member 3 of a special construction. By a cylindrical valve part 26 peripherally provided on the inner peripheral edge of a partition wall 28 partitioning an air pressurizing chamber A, a vent path 48 connecting the inside of a large-diameter air cylinder 14 to a liquid path 45 is blocked unless air is introduced into the liquid path 45 through the large-diameter cylinder.

